



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Flow behavior and glass forming ability of calcium aluminosilicate melts

Moesgaard, Mette; Yue, Yuanzheng

Publication date:
2008

Document Version
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Moesgaard, M., & Yue, Y. (2008). *Flow behavior and glass forming ability of calcium aluminosilicate melts*. Abstract from 4th Balkan Conference on Glass Science Technology, Varna, Bulgaria.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

FLOW BEHAVIOR AND GLASS FORMING ABILITY OF CALCIUM ALUMINOSILICATE MELTS

Mette Moesgaard, Yuanzheng Yue

Section for Chemistry, Aalborg University, Sohngaardsholmsvej 57
DK-9000 Aalborg, Denmark (mm@bio.aau.dk)

The relation between flow behavior and glass forming ability has been investigated for 10 calcium aluminosilicate (CAS) melts. Five melts include the two eutectic compositions of the anorthite-wollastonite-gehlenite and the anorthite-wollastonite-tridymite triangles, and three on the joining line between the two. The other five melts lie on a line parallel to the joining line. The temperature dependences of the viscosity are determined in the low viscosity range (approx. 10^0 - 10^2 Pa s) using concentric cylinder viscometry, and, in the high viscosity range (approx. 10^9 - 10^{13} Pa s) using micro penetration viscometry. The fragility parameters of the melts are obtained by fitting the viscosity data to the Avramov equation. These parameters along with crystallization behavior and working temperatures are used to define and evaluate the glass forming ability of the CAS melts. To reveal the structural origin of the flow behavior, the ten glasses are characterized using ^{29}Si and ^{27}Al solid state nuclear magnetic resonance spectroscopy. The final purpose of this study is to find an optimum composition for ensuring both good glass forming ability and qualified physical and chemical performances for a technical application within an industrial project.